

# KITCHEN TOWEL SCARF

12-21 JELLY ROLL STRIPS –YOU CAN DOUBLE-UP CUTTING 2 FROM 10 STRIPS- OR CUT ONE EACH FROM 20 STRIPS  
KITCHEN TOWEL APPROXIMATE SIZE - 20" WIDE BY 30" HIGH  
2 ½" YARD OF LIGHTWEIGHT FUSIBLE INTERFACING – PELLON SHAPE FLEX  
ONE – ¾" – 1"BUTTON TO MATCH YOUR FABRICS

CUT 10 – 20 JELLY ROLL STRIPS INTO 2 ½" X 13" OR 2 ½" X 21". PLACE YOUR 20 STRIPS IN YOUR FAVORITE ORDER.  
SEW ALL STRIPS TOGETHER ON THE 13" SIDES - ¼" SEAM ALLOWANCE. PRESS SEAMS OPEN STRIPS SHOULD MEASURE  
37"-38" X 13". TRIM THE 13" SIDE TO 11 ½" WIDE. . PLACE PATCHWORK PANEL ON INTERFACING AND CUT TO MATCH  
PANEL SIZE – FUSE TO WRONG SIDE OF PATCHWORK PANEL.

TOWEL – FOLD THE 30" HIGH LENGTH IN HALF AND CUT – MAKING 2 TOWELS – 20" WIDE X 15" HIGH.

ACCENT TOWEL BANDS - MEASURE YOUR TOWEL WIDTH – ADD 2" TO THIS NUMBER AND CUT THIS MEASUREMENT  
FROM THE 2 ½" X 40" STRIP – YOU WILL HAVE 2 BANDS. PRESS EACH LONG SIDE UNDER ½". CUT 2 INTERFACING 1 3/8"  
WIDE X LENGTH OF STRIP AND FUSE BETWEEN THE FOLDED SIDES. MEASURE FROM FINISHED BOTTOM EDGE OF TOWEL  
2" UP TO PLACE THE BOTTOM EDGE OF THE ACCENT TOWEL BANDS. TUCK LEFT AND RIGHT ENDS OF BANDS UNDER  
STRIP –PIN AND TOPSTITCH BAND DOWN.

ACORDIAN FOLD THE TOWEL IN HALVES CREATING FINISHED WIDTH APPROX. 5". FOLD TOWEL IN HALF RIGHT SIDES  
TOGETHERS AND PRESS LIGHTLY TO SET A CREASE LINE AT TOP. OPEN THE TOWEL WRONG SIDE UP ON FLAT SURFACE.  
FOLD EACH SIDE TO MIDDLE CREASE LINE. FOLD IN HALF ONCE AGAIN. YOU WILL HAVE FOLDS ALONG 15" SIDE AND  
ONE FOLD AND BOTH HEMMED EDGES ALONG THE OPPOSITE 15" SIDE. THE WIDTH SHOULD FINISH ABOUT 5". ONE  
END IS THE BOTTOM HEMMED EDGE OF THE TOWEL AND THE OPPOSITE END IS THE RAW CUT EDGE.

BUTTON LOOP – 2" X 4" – FOLD THE STRIP IN HALF AND PRESS. FOLD RAW EDGE TOWARD CENTER AND PRESS.  
TOP STITCH. PLACE BUTTON LOOP RIGHT SIDE UP OVER THE FIRST SEAM ON THE LEFT SIDE OF THE PATCHWORK PANEL.

FOLD PATCHWORK PANEL IN HALF WRONG SIDES TOGETHER ALONG HORIZONTAL CENTER. PRESS LIGHTLY TO FORM A  
CENTER CREASE LINE. RIGHT SIDE UP ON FLAT SURFACE. PLACE THE ACCORDION FOLDED TOWEL HALF ON EACH SIDE.  
THE HEMMED SIDE OF THE TOWEL HALVES SHOULD SIT ROGHT ALONG THE CENTER CREASE LINE. THE RAW ENDS OF THE  
TOWEL HALVES SHOULD BE FLUSH WITH THE RAW SIDES OF THE PATCHWORK PANEL. THE FOLDED SIDES OF THE TWOEL  
HALVES SHOULD SIT JUST OVER ½" IN FROM THE RAW BOTTOM EDGE OF THE PATCHWORK PANEL.

BASTE TOWELS EDGES 3/8" SEAM ALLOWANCE TO PATCHWORK PANEL. FOLD THE PANEL IN HALF – RIGHT SIDES  
TOGETHER ALONG HORIZONTAL CENTER LINE SANDWICHING THE TOWEL HALVES BETWEEN THE LAYERS. LINE UP  
PATCHWORK SEAMS. PIN ALONG BOTH SIDES AND ACROSS THE BOTTOM LEAVING APPROXIMATE 4" OPENING TURN  
GAP IN THE CENTER OF THE LONG BOTTOM SEAM. SEW ½" SEAM ALLOWANCE. CLIP AND TRIM THE CORNERS. TURN  
RIGHT SIDE OUT AND PRESS RAW EDGE FLUSH AND TOP STITCH.

USE BUTTON LOOP TO MAKE BUTTON PLACEMENT. SEW BUTTON ON.

BONUS – YOU CAN USE A SOLID PIECE OF FABRIC TO CREATE THE PATCHWORK PANEL – 11 ½" WIDE X 38" LONG.  
DIRECTIONAL FABRICS WILL REQUIRE SPECIAL CUTTING. FOLLOW ABOVE DIRECTIONS.